

VIVID™ For Stone

SOLVENT FREE ENHANCING SEALER

BENEFITS

- Provides excellent water repellency to reduce cracking, spalling, freeze/thaw damage, chemical degradation, biological growth, efflorescence, and dirt pickup, thereby lengthening substrate life and reducing maintenance costs.
- Low VOC
- Formulated to impart an enhanced appearance on stone and natural tile substrates
- Formulated to provide either a matte finish or a gloss finish, depending upon application.
- 20 YEAR UV and stain resistance
- Bonds physically and chemically
- Vapor permeable resists cracking, peeling, and blistering
- Non-Flammable – Flash Point > 200° F

DESCRIPTION VIVID™ for Stone is a stable, VOC Compliant, 100% active siloxanes/silicone resin blend that imparts water and stain repellency to substrates while providing an enhanced look. VIVID for Stone is produced in the USA, was developed to treat a wide variety of mineral substrates commonly used in the tile industry including tumbled marble, limestone, slate and saltillo clay tile. **Test application** is recommended on surface to be treated to ensure compatibility and repellent result. Typical property values are not intended for use in the preparation of specifications. A test patch should be performed prior to general application with the customer's approval to ensure the desired appearance is achieved.

WARNINGS: Do not dilute or alter. Protect from freezing. Use eye protection and minimize skin contact with gloves and clothing. Protect all adjacent and non-targeted surfaces from contamination. Use in well-ventilated area away from sparks and open flame. Do not smoke in vicinity of application. Do not store or use near sparks or open flames.

USAGE: Can be used on all natural stone including marble, limestone, saltillo clay tile and slate.

APPLICATION: Do not spray apply product. Surface should be free of standing water, dirt, dust, oils & other contaminants. VIVID for Stone should be applied as supplied to achieve the desired application effect. One to two coats of the solutions should be applied to achieve an enhanced appearance. Two to three coats of the solution should be applied to achieve an enhanced appearance with gloss.

Method: Apply with soft, lint-free cloth, sponge, or paint brush. Excess material should be removed to prevent inconsistencies in the enhancement.

Surface Preparation: Surface preparation depends on substrate placement, type and strength, curing and finishing processes, age, condition, previous contamination and the presence of existing coatings as well as the application of VIVID for Stone. Surfaces should be clean from dust, dirt, oils, grease, cutting compounds, other coatings, efflorescence and laitance before applying VIVID for Stone.

DRY TIME: VIVID for Stone should be fully cured within 24 hours

CLEAN UP: Thoroughly rinse application equipment with solvent.

STORAGE: One (1) year shelf life-unopened. VIVID for Stone must be stored in tightly closed containers, protected from sunlight and stored at temperatures between 32°F (0°C) and 100°F (38°C).

COVERAGE: 200– 2000 sq ft per gallon depending on surface porosity, density and desired finish

Contact VanHearron Technical Services for further information or application instructions 479 255-6101.

Disclaimer/Warranties: Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container that the product comes in. No implied warranties including, but not limited to, an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to be determine suitability of the product for the intended use and user assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.